



Finish Care and Cleaning:

Clear-coated finishes should be wiped with a soft, damp cloth. A mild soap may be lightly used if very dirty. Particular care should be taken to avoid paint smears, thinners and strong cleaning agents as they will quickly destroy the protective coatings and subject the finish to rapid oxidation and discoloration. Initial care for finishes requires only periodic cleaning with mild non-abrasive soap and light buffing with a soft cloth.

Lock and mechanical parts care and maintenance:

TRILENNIUM products should remain clean of dirt, saw dust, paints, stains and other debris and/ or substances that interfere with any of the mechanical components of the product. In order to ensure proper latch engagement and smooth operation, the lock latches should be inspected annually. A little spray of silicone (not WD-40) around the latches is good routine maintenance. In addition, the strike plate rollers should be inspected annually to ensure proper lock system operation. A little spray of silicone (not WD-40) on the roller shaft is good routine maintenance. A light film of white grease or Vaseline on the bolt tips (where they contact the strikes) will help ensure that the latches retract smoothly.

CAUTION!

Always follow the below guidelines during fabrication, installation or daily use of the Trilennium lock:

- The lock must be installed in properly machined door panels, with sufficient clearance space for all moving parts
- All visible screws on the lock and handle set should not be over-tightened with an electric or pneumatic drill, but rather installed snug with a hand screw driver
- During (re)finishing of the door unit (painting or staining), the lock should be removed from the door to protect it from and exposure to paint/ stain
- Never use abrasive cleaning tools (such as household sponges or brushes) to clean any parts of the Trilennium lock or hardware
- Never use commercial or residential cleaning solvents, paint thinners, acetone, or other strong cleaning agents to clean the Trilennium lock or hardware
- DO NOT use the Trilennium handle set to lift the door in case of a sagging door panel
- In case of malfunctioning lock or handle set, DO NOT attempt to repair or adjust the lock mechanism without contacting a local distributor or an Endura representative



PERFORMANCE STANDARD

8817 W. Market St., Colfax, NC 27235
1.800.334.2006 www.enduraproducts.com